

A Review on Cognitive Radio Sensor Networks for Internet of Things

Abhinav Shukla^{1,*}, Hemant Rajoriya², Ambresh Patel³

Abstract

Cognitive radio sensor networks (CRSNs) can effectively manage communication through clustering. This paper examines Internet of Things Cognitive Radio Sensor Networks. An important step towards a world of smart technology is the Internet of Things (IoT) system based on Cognitive Radio (CR). Many frameworks for creating CR-based IoT systems have been put forth. IoT frameworks based on CR are the main topic of the survey. One possible approach to improving the effectiveness of wireless communication in the Internet of Things (IoT) is the use of Cognitive Radio Sensor Networks (CRSNs). The increasing number of IoT devices cannot be supported by traditional wireless sensor networks due to issues like interference and spectrum constraint. By using cognitive radio technology, CRSNs solve these problems by enabling sensors to dynamically sense, adjust, and use available frequency bands. Although CRSNs have many advantages, there are various difficulties associated with their implementation. Managing the spectrum is still a vital concern, necessitating efficient policies and algorithms to control access to the spectrum and prevent clashes with primary users. Moreover, energy limitations present a challenge because IoT devices need to function effectively within restricted power supplies. Concerns about security, including breaches of data and unauthorized access, necessitate effective countermeasures to safeguard the integrity of the network. This analysis examines the design, essential elements, and operational concepts of CRSNs, emphasizing how they enhance network performance and spectrum efficiency. It talks about the benefits of CRSNs, such as improved energy efficiency, communication dependability, and flexibility under changing conditions. We also examine the difficulties in implementing CRSNs, including spectrum management issues, energy limitations, and security concerns.

Keywords: Internet of Things, Cognitive Radio, Wireless Sensor Networks, Clustering Protocol, WI MAX.

*Author for Correspondence

Abhinav Shukla
E-mail: abhinav.shukla@hotmail.com,

¹Assistant Professor, Department of Electronics and Communication Engineering, Veda Institute of Technology, Bhopal

²Assistant Professor, Department of Electronics and Communication Engineering, Ram Krishna Dharmarth Foundation University, Bhopal

³Assistant Professor, Department of Electronics and Communication Engineering, Sri Satya Sai College of Engineering, Bhopal

Received Date: March 11, 2025

Accepted Date: March 20, 2025

Published Date: March 29, 2025

Citation: Abhinav Shukla, Hemant Rajoriya, Ambresh Patel. A Review on Cognitive Radio Sensor Networks for Internet of Things. International Journal of Broadband Cellular Communication. 2025; 11(1): 30–34p.

INTRODUCTION

Cognitive sensor technology that allows cognitive sensors (CSs) to access randomly licensed channels is suggested in light of the severe increase in demand for wireless services and the limited availability of spectrum resources. Many people consider radio sensor networks (CRSNs) to be a viable option for reliable and effective wireless Internet networks (IoT).

An effective technique for controlling connections to CRSNs is clustering. In order to guarantee the proper organization of spectrum-aware connections, Integrated CRSN assigns local coordinators to oversee the network. However, because spectrum dynamics cause the typical topology variation of CRSNs, existing methods suffer from high frequency interactions. The

number of devices connected to the Internet has increased as a result of technological advancements. By 2020, there will be 200 billion connected devices, up from 2 billion in 2006, according to Intel. By 2020, 75% of automobiles will have an Internet of Things (IoT) connection, predicts Business Insider.

Therefore, a lot of new problems arise every day as a result of the Internet of Things' (IoT) unprecedented growth in the number of devices connected to the Internet. Today, IoT applications are everywhere. In recent years, a number of new IoT-related objectives have surfaced, such as smart industries, smart transportation, smart agriculture, smart cities, smart homes, and smart living. Therefore, putting IoT systems into place will save a lot of money and generate income in many areas, especially in keeping an eye on things and providing maintenance services. As a result, these growths have compelled businesses to implement a variety of strategies to address dynamic growth and associated challenges, such as allocating adequate spectrum belts to IoT systems. These include poor transmission performance, insufficient spectrum, spectrum sharing, device interference, and so on. In recent years, the implementation of Cognitive Radio Networks (CRNs) on the Internet of Things has shown comparable or superior performance to that of currently used networks like Bluetooth, Wi-Fi, and WI MAX. In order to create concerning spectrum resources, one of the main challenges is figuring out how to regulate and manage the Radio Frequency (RF) spectrum. As wireless communication systems expand at an unprecedented rate, users and applications are consuming more spectrum, which makes it crucial for connected devices to communicate with one another. Consequently, there is a growing need for intelligent gadgets that can control and modify transmission limits by detecting spectrum in spatiotemporal sizes. Cognitive Radio (CR), a versatile radio and network technology that automatically recognizes wireless spectrum channels and modifies transmission parameters to allow for more communication while enhancing radio behavior, is the best candidate technology. The four stages of CR's awareness cycle are hearing, sharing, mobility, and decision-making. The SS phase, which begins the perception cycle, uses a variety of SS techniques to acquire available spectrum resources over the selected spectrum band. Either the band should be shared or the transfer to that band should be stopped, depending on the acquisition results. In order to guarantee PU protection, power allocation should be considered and the proper Medium Access Control (MAC) protocol used if CR chooses to use the band. Last but not least, the movement phase is used to switch between bands. The main design characteristics of CR-based IoT systems are covered in this work first. Additionally, the study examines the latest research on spectrum sharing and SS, separates them, talks about how they are used in the Internet of Things, and presents the best MAC protocol and SS technique for the IoT system based on -CR. Additionally, the MAC protocols utilized in this field are analysed and contrasted by this function.

Literature Review

Meng Zheng, et al. [1] encourages CRSNs to use the network stability-aware clustering (NSAC) protocol. For the first time, spectrum dynamics and energy consumption are incorporated into the design of the NSAC protocol. Extensive mimicking shows that the suggested NSAC protocol performs noticeably better than current methods in terms of power consumption and network stability.

FAROQ A et al. [2] outlines hearing and sharing techniques and talks about their suitability and constraints. The design characteristics of CR-based IoT are also covered in this survey, along with advice on selecting the most effective SS and access techniques. The survey also examines the integration of CR-based IoT systems with new and developing technologies. The survey ends with open-ended questions and suggestions for additional research after discussing some of the new issues.

Heejung et al. [3] highlights the difficulties facing the upcoming generation of IoT networks, which need to increase output without compromising reliability while continuously lowering overall network latency. Utilizing various frequencies for networking is an additional choice. But supplying data bandwidth and guaranteeing spectrum availability are difficult tasks. Therefore, the best technology to handle all of the issues of IoT, WSN, 5G, and beyond is understanding radio networks (CRN).

W.S Ahmed et al. [4] The objective is to perform a comprehensive analysis of the latest 5G-enabling technology and spectrum-sharing technology (SS) in development. In addition to reviewing surveys

and studies on SS strategies for 5G networks, SS strategies are categorized. The three primary SS methods were determined by the network structure, spectrum distribution behavior, and spectrum access method of the surveys and studies. Additionally, there is a comprehensive study being conducted on radio technology (CR) in SS in relation to the deployment of 5G.

Abdelmohsen et al. [5] Key methods are classified according to radio parameters. We then examine the current spectrum sensor functions utilized in different categories, including collaboration sensors, narrowband sensing, narrowband spectrum monitoring, wideband sensing, and practical application considerations for different techniques. Finally, we examine the latest levels based on the interweave network model. Furthermore, we outline the most recent advancements in asset spectrum sensing methodology. We end this survey paper by outlining some unrestricted research questions and recommendations for CR networks in applications for the next generation of the Internet of Things.

Antoni et al. [6] provides a detailed analysis of the spectrum sensitivity mechanisms that are discernible from received signal samples by a factor that extracts them to give the main user (PU) accurate signal processing. The main characteristics of each type are outlined, along with their advantages and disadvantages, including computer complexity, model/sound prediction, probability, intensity, and dimension. A wireless approach-based method is presented to elucidate the function of spectrum-based CR in future networks, based on existing 6G network and application concepts.

Erick et al. [7] has provided an overview of the needs of smart cities established by Cooperative Sensor Networks. Based on the challenges due to emerging needs and rapid technological advancement, the front radio frequency (RF) transmitter must restructure its normal configuration in order to achieve service integration. An RF-frontend architecture solution for a system based on the Internet sensor network is proposed. It has been suggested that modern technology should be developed in terms of spectrum allocation, operational bandwidth and energy consumption.

Simon Haykin and Peyman Setoodeh [8] explore different approaches to managing spectrum access in wireless networks, focusing on two distinct models: open-access and market-driven spectrum allocation. Each model offers unique advantages and is better suited to specific scenarios, highlighting their complementary roles in spectrum management. The authors present analytical models that help in understanding both the steady-state (equilibrium) and dynamic (transient) behaviours of these networks. Their research provides valuable insights into optimizing spectrum utilization, ensuring efficient communication in various network environments.

Ayaz Ahmad et al. [9] present a comprehensive review of recent advancements in radio resource allocation for Cognitive Radio Sensor Networks (CRSNs). Resource allocation strategies are categorized into three primary types: centralized, cluster-based, and distributed approaches. Each category undergoes further examination based on crucial performance optimization factors, including energy efficiency, throughput enhancement, quality of service (QoS) assurance, interference mitigation, fairness, priority handling, and handoff reduction. Their research provides valuable insights into the various methodologies employed to optimize radio resource allocation, aiding in the efficient functioning of CRSNs.

Design Factors of CR-Based IoT Systems

The primary goal of an Internet of Things (IoT) system is to create seamless connectivity between various devices and platforms while ensuring efficient resource usage. Factors such as cost, power consumption, and hardware complexity must be minimized without compromising performance. Maintaining uninterrupted connectivity is essential for IoT networks to function effectively, which highlights the importance of efficient spectrum utilization and signal sensing (SS) mechanisms in CR-based IoT systems.

For a CR-enabled IoT device, selecting an optimal SS strategy is crucial to ensure smooth communication while adhering to spectrum-sharing protocols. Additionally, designers must allocate

spectrum bands carefully, making use of available frequency gaps while ensuring minimal disruption to primary users (PUs). To achieve these objectives, the following aspects must be considered:

- *IoT Applications:* The specific use cases and requirements of IoT solutions must be analyzed to determine the most suitable network and communication strategies.
- *Enabling Technologies:* The integration of CR with IoT requires leveraging advanced technologies such as artificial intelligence, machine learning, and cloud computing for effective spectrum management.
- *Regulatory Compliance:* IoT systems must adhere to spectrum allocation and usage policies defined by governing authorities to prevent interference and ensure efficient coexistence with existing communication networks.

Applications of IoT in Smart Systems

IoT technology is revolutionizing various sectors by enabling automation, smart decision-making, and real-time data exchange. Some key applications include:

- *Smart Access Control Systems:* Automated security systems for doors that use sensors and wireless authentication to control entry.
- *Intelligent Lighting Solutions:* Energy-efficient lighting systems for homes and offices that adjust brightness based on occupancy and ambient conditions.
- *Automated Garage and Gate Control:* Remote-controlled and sensor-driven gate and garage door automation for improved security and convenience.
- *Climate Control Systems:* Smart humidity controllers and thermostats that optimize indoor climate settings based on environmental conditions.
- *Traffic Management Systems:* IoT-enabled traffic monitoring and control solutions that help optimize vehicle movement and reduce congestion.
- *Smart Street Lighting:* Adaptive lighting systems that adjust brightness based on traffic flow and pedestrian activity to conserve energy.
- *Environmental Monitoring:* Sensors that track air pollution levels and report real-time data for better urban air quality management.
- *Smart Parking Solutions:* IoT-based parking systems that help drivers locate available parking spots and optimize space usage.

These applications demonstrate how IoT, combined with cognitive radio technology, can significantly enhance automation, efficiency, and sustainability in various domains.

CONCLUSION

To the best of our knowledge, this paper looks at all the methods that deal with the spectrum allocation/CRIOT editing problem. It should be noted that while most IoT configurations do not use this number, the majority of research in this field does. One new way to increase the number of IoTs is to add edge nodes that can control the number of IoTs in order to control channel planning and CRN allocation.

REFERENCES

1. Zheng M, Chen S, Liang W, Song M. NSAC: A novel clustering protocol in cognitive radio sensor networks for Internet of Things. *IEEE Internet of Things Journal*. 2019 Feb 8;6(3):5864-5.
2. Awin FA, Alginahi YM, Abdel-Raheem E, Tepe K. Technical issues on cognitive radio-based Internet of Things systems: A survey. *IEEE access*. 2019 Jul 19;7:97887-908.
3. Yu H, Zikria YB. Cognitive radio networks for internet of things and wireless sensor networks. *Sensors*. 2020 Sep 16;20(18):5288.
4. Ahmad WS, Radzi NA, Samidi FS, Ismail A, Abdullah F, Jamaludin MZ, Zakaria M. 5G technology: Towards dynamic spectrum sharing using cognitive radio networks. *IEEE access*. 2020 Jan 13;8:14460-88.
5. Ali A, Hamouda W. Advances on spectrum sensing for cognitive radio networks: Theory and applications. *IEEE communications surveys & tutorials*. 2016 Nov 18;19(2):1277-304.

6. Ivanov A, Tonchev K, Poulkov V, Manolova A. Probabilistic spectrum sensing based on feature detection for 6G cognitive radio: A survey. *IEEE Access*. 2021 Aug 18;9:116994-7026.
7. González-Rodríguez E, Maune H, Shen L, Shah IA, Dahlhaus D, Hofmann K, Jakoby R. Reconfigurable radio frontends for cooperative sensor networks: Tasks and challenges. In 2013 IEEE 14th Workshop on Signal Processing Advances in Wireless Communications (SPAWC) 2013 Jun 16 (pp. 515-519). IEEE.
8. Haykin S, Setoodeh P. Cognitive radio networks: The spectrum supply chain paradigm. *IEEE Transactions on Cognitive Communications and Networking*. 2015 Mar;1(1):3-28.
9. Ahmad A, Ahmad S, Rehmani MH, Hassan NU. A survey on radio resource allocation in cognitive radio sensor networks. *IEEE Communications Surveys & Tutorials*. 2015 Feb 9;17(2):888-917.
10. Kakkavas G, Tsitseklis K, Karyotis V, Papavassiliou S. A software defined radio cross-layer resource allocation approach for cognitive radio networks: From theory to practice. *IEEE Transactions on Cognitive Communications and Networking*. 2020 Jan 3;6(2):740-55.